

FILETTATURA WHITWORTH BSW

Conforme a BS 84 - tolleranza media

Dimen- sione	Passo F x 1"	MADREVITE				VITE					
		medio		nocciolo Ø foratura		esterno Ø tornitura		medio		nocciolo	
		min.	max	min.	max	max	min.	max	min.	max	min.
1/4	20	5,537	5,650	4,744	5,224	6,330	6,000	5,537	5,424	4,724	4,422
5/16	18	7,034	7,153	6,151	6,661	7,918	7,600	7,034	6,915	6,131	5,813
3/8	16	8,509	8,636	7,512	8,052	9,505	9,100	8,509	8,382	7,492	7,154
7/16	14	9,951	10,086	8,809	9,379	11,093	10,700	9,951	9,816	8,789	8,430
1/2	12	11,345	11,491	10,015	10,610	12,675	12,200	11,345	11,199	9,990	9,600
5/8	11	14,397	14,550	12,948	13,598	15,846	15,400	14,397	14,244	12,918	12,510
3/4	10	17,424	17,584	15,831	16,538	19,018	18,500	17,424	17,264	15,798	15,371
7/8	9	20,419	20,588	18,647	19,411	22,190	21,600	20,419	20,250	18,611	18,161
1"	8	23,368	23,547	21,375	22,185	25,361	24,800	23,368	23,189	21,335	20,858
1 1/8	7	26,253	26,444	23,976	24,879	28,529	27,900	26,253	26,062	23,929	23,419
1 1/4	7	29,428	29,619	27,151	28,054	31,704	31,000	29,428	29,237	27,104	26,594
1 3/8	6	32,215	32,422	29,558	30,555	34,873	34,100	32,215	32,008	29,505	28,953
1 1/2	6	35,391	35,598	32,733	33,730	38,048	37,300	35,391	35,184	32,680	32,128
1 5/8	5	38,024	38,251	34,834	35,921	41,214	40,300	38,024	37,797	34,771	34,166
1 3/4	5	41,199	41,426	38,009	39,096	44,389	43,500	41,199	40,972	37,946	37,341
1 7/8	4 1/2	44,012	44,251	40,468	41,648	47,557	46,600	44,012	43,773	40,398	39,761
2"	4 1/2	47,187	47,426	43,643	44,823	50,732	49,800	47,187	46,948	43,573	42,936
2 1/4	4	53,086	53,339	49,100	50,420	57,072	56,200	53,086	52,833	49,020	48,345
2 1/2	4	59,436	59,689	55,450	56,770	63,422	62,500	59,436	59,183	55,370	54,695
2 3/4	3 1/2	65,205	65,476	60,648	62,108	69,763	68,800	65,205	64,934	60,558	59,836
3"	3 1/2	71,556	71,827	66,699	68,459	76,113	75,100	71,556	71,285	66,909	66,187